

Fișă tehnică produs

Specificatii

Limitator cuplu - accesorii de instalare - 9 N.m - set de 6



LV426990

Principale

Gama	PowerPact
gama de produse	ComPact NSXm
Tip produs sau componenta	Torque limiting breakaway bit
categorii accesorii / piese de schimb	Accesoriu de instalare
Compatibilitate gama	Compact (ComPact NSXm) PowerPact (PowerPact B) TeSys (TeSys GV3) TeSys (TeSys GV4) TeSys (TeSys BV4)
Cantitate pe set	Set de 6
culoare	Verde
cuplu de strangere	9 N.m

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	1,5 cm
Latime prima forma de impachetare	5,5 cm
Lungime prima forma de impachetare	7,0 cm
Greutate prima forma de impachetare	69,0 g
Unitate de masura pentru a doua forma de impachetare	S02
Numar unitati in a doua forma de impachetare	120
Inaltime a doua forma de impachetare	15,0 cm
Latime a doua forma de impachetare	30,0 cm
Lungime a doua forma de impachetare	40,0 cm
Greutate a doua forma de impachetare	8,28 kg

Garanție contractuală

Garantie	18 luni
----------	---------

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Use Better

 Materiale si ambalare	
Continut de metal reciclat	0
Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS)
Regulamentul REACH	Declaratia REACH
Performanta continutului de halogen	Produs cu piese din plastic fara halogen

Use Again

 Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	No

Offer Marketing Illustration

Product benefits / Features



Compact NSXm

Range Accessories



Wireless indication auxiliary



Long terminal shield



Standard auxiliary contact



Rotary handles



Inter-phase barrier



Toggle padlocking device



MN undervoltage release



Standard MX shunt release

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm

Moulded Case Circuit Breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features



CompacT NSX

Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker = ELCB)
- EverLink™ connectors for bare cables