



Adaptor De Blocare Cu Lacat Comutator Amovibil - Pt. Ns80 - 630

29370

Principale

Compatibilitate gama	Compact (ComPact NSXm) Compact (ComPact NSX100) Compact (ComPact NSX160) Compact (ComPact NSX250) Compact (ComPact NSX400) Compact (ComPact NSX630) EasyPact (EasyPact CVS100) EasyPact (EasyPact CVS160) EasyPact (EasyPact CVS250) PowerPact (PowerPact B) TeSys (TeSys GV4) TeSys (TeSys BV4) Compact Compact NSX100 DC Compact Compact NSX160 DC Compact Compact NSX250 DC Compact (Compact NSF250) Compact (Compact NSJ400) Compact (Compact NSJ600) Compact (Compact NSX500) Compact (Compact NB400) Compact (Compact NB600)
Tip produs sau componenta	Dispozitiv de blocare cu lacat
nume scurt al dispozitivului	inchidere pentru 1 pana la 3 lacate

Suplimentare

tip de accesorii / piese separate	Accesoriiincuietori
mod de montare	Amovibil
destinatie incuietoare cu cheie	Comutare
numar de incuietori	3
pozitie de blocare cheie	In fata
descriere optiuni de blocare	Incuietoare numai dezactivata Intre 1 si 3 lacate Amovibil

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	1,000 cm
Latime prima forma de impachetare	10,000 cm
Lungime prima forma de impachetare	13,000 cm
Greutate prima forma de impachetare	41,600 g

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

Unitate de masura pentru a doua forma de impachetare	S03
Numar unitati in a doua forma de impachetare	40
Inaltime a doua forma de impachetare	30,000 cm
Latime a doua forma de impachetare	30,000 cm
Lungime a doua forma de impachetare	40,000 cm
Greutate a doua forma de impachetare	2,064 kg
Unitate de masura pentru a treia forma de impachetare	P12
Numar unitati in a treia forma de impachetare	320
Inaltime a treia forma de impachetare	50,000 cm
Latime a treia forma de impachetare	80,000 cm
Lungime a treia forma de impachetare	120,000 cm
Greutate a treia forma de impachetare	27,312 kg

Garanție contractuală

Garantie	18 months
----------	-----------



Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Use Better

🔍 Materiale si ambalare	
Continut de metal reciclat	0
Pachet cu carton reciclabil	Da
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS)
Regulamentul REACH	Declaratia REACH

Use Again

🔄 Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	No

Offer Marketing Illustration

Product benefits / Features



Compact NSXm

Range Accessories



Wireless indication auxiliary



Long terminal shield



Standard auxiliary contact



Rotary handles



Inter-phase barrier



Toggle padlocking device



MN undervoltage release



Standard MX shunt release

Offer Marketing Illustration

Product benefits / Features



CompacT NSX

Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents; 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker = ELCB)
- EverLink™ connectors for bare cables

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm

Moulded Case Circuit Breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

