

Set distrib. - pas 35 mm - 3 coloane

LV426940



Principale

Compatibilitate gama	PowerPact (PowerPact B) Compact (ComPact NSXm) TeSys (TeSys GV4) TeSys (TeSys BV4)
Tip produs sau componenta	Distribuitoare

Suplimentare

tip de accesorii / piese separate	Accesorii de conectare
descriere poli	3P
Cantitate pe set	Set de 1
echipament furnizat	Interphase barriers
mod de montare	Fix
locul conexiunii	Aval Amonte
[In] calibru	160 A
pasul conexiunii	35 mm
material conductor	Aramiu
conexiuni - borne	Crimp lug (amonte) Crimp lug (aval)
cuplu de strangere	9 N.m amonte 9 N.m aval

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	1,500 cm
Latime prima forma de impachetare	7,000 cm
Lungime prima forma de impachetare	9,000 cm
Greutate prima forma de impachetare	172,000 g
Unitate de masura pentru a doua forma de impachetare	S02
Numar unitati in a doua forma de impachetare	26
Inaltime a doua forma de impachetare	15,000 cm
Latime a doua forma de impachetare	30,000 cm

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

Lungime a doua forma de impachetare	40,000 cm
Greutate a doua forma de impachetare	4,740 kg

Garanție contractuală

Garantie	18 luni
----------	---------

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Use Better

 Materiale si ambalare	
Pachet cu carton reciclabil	Nu
Ambalaj fara plastic	Nu
Directiva RoHS UE	Conform
Regulamentul REACH	Declaratia REACH

Use Again

 Reambalare si refabricare	
Preluare la sfarsitul duratei de viata	No
DEEE	 Produsul trebuie sa fie eliminat de pe piata din Uniunea Europeana dupa colectarea specifica a deseurilor si sa nu ajunga niciodata in pubele de gunoi

Offer Marketing Illustration

Product benefits / Features



CompacT NSX

Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker = ELCB)
- EverLink™ connectors for bare cables

Offer Marketing Illustration

Product benefits / Features



Compact NSXm

Range Accessories



Wireless indication auxiliary



Long terminal shield



Standard auxiliary contact



Rotary handles



Inter-phase barrier



Toggle padlocking device



MN undervoltage release



Standard MX shunt release

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm

Moulded Case Circuit Breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.

