

Fișă tehnică produs

Specificatii



bec Led Protejat cu baza Ba15D, Continuu, Rosu, 24 V

DL1BDB4

⚠ Fabricatie intrerupta la data de: 5 nov. 2024

⚠ Finalul ciclului de service: 31 dec. 2025

⚠ Va fi retras de la
comercializare

Principale

Compatibilitate gama	Harmony XVP Harmony XVD Harmony XVB
denumire accesori/piese separate	Bec protejat cu LED
tip de accesorii / piese separate	Bec cu LED
categorii accesorii / piese de schimb	Accesorii iluminat
destinatie accesorii/piese separate	Girofar si baterie de indicatoare
[Us] tensiune nominala de alimentare	24 V c.a./c.c.
tip semnalizare	Stabil
culoare semnalizare	Rosu
cantitate indivizibila de vanzare	1

Suplimentare

consum de curent	47 mA
baza bec	BA 15d
greutate produs	0,015 kg

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	3,500 cm
Latime prima forma de impachetare	4,500 cm
Lungime prima forma de impachetare	6,000 cm
Greutate prima forma de impachetare	11,000 g
Unitate de masura pentru a doua forma de impachetare	S01
Numar unitati in a doua forma de impachetare	60
Inaltime a doua forma de impachetare	15,000 cm
Latime a doua forma de impachetare	15,000 cm
Lungime a doua forma de impachetare	40,000 cm

Greutate a doua forma de impachetare	960,000 g
---	-----------

Garanție contractuală

Garantie	18 luni
----------	---------

Environmental Data

Schneider Electric isi propune sa atinga nivelul Net Zero pana in 2050 prin parteneriate la nivelul lantului de aprovizionare, materiale cu impact mai redus si circularitate, prin campania „Use Better, Use Longer, Use Again” pentru a extinde durata de viata a produselor si reciclabilitatea.

[Environmental Data explicate >](#)

[Cum evaluam sustenabilitatea produselor >](#)

Amprenta de mediu

Amprenta de carbon (kg CO2 eq.)	34
---------------------------------	----

Use Better

Materiale si ambalare

Pachet cu carton reciclabil	Da
-----------------------------	----

Ambalaj fara plastic	Da
----------------------	----

[Directiva RoHS UE](#)

Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS)

Regulamentul REACH

[Declaratia REACH](#)


Use Again

Reambalare si refabricare

Profil circularitate	Nu sunt necesare operatii de reciclare speciale
----------------------	---

Preluare la sfarsitul duratei de viata	No
--	----

DEEE

 Produsul trebuie sa fie eliminat de pe piata din Uniunea Europeana dupa colectarea specifica a deseurilor si sa nu ajunga niciodata in pubele de gunoi

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XVB

Robust product performance with high IP protection and IK05 shock resistance



Greater loudness up to 90dB with continuous and intermittent tones



Conformity with International standards



Beacon lens on top with high intensity 5J, 10J Xenon flash, increase visibility from top and surrounding



Offer Marketing Illustration

Product benefits / Features

The infographic features a central image of two Harmony XVB light fixtures: one with five stacked lens units in red, yellow, green, blue, and white, and another with a single red lens unit. The background is a vibrant green. The title 'Features Harmony XVB' is at the top center. Five circular icons are arranged around the central image, each with a corresponding text block describing a feature. The icons include a lightbulb, a lightbulb with a lightning bolt, crossed wrench and screwdriver, a checkmark, and a leaf.

Features Harmony XVB

- 3 types of light source:** 10-Watt incandescent bulb, built-in high-efficiency LEDs, 5 and 10-joule discharge tube
- 100,000 hours of maintenance-free lighting** thanks to "LED Protected" technology
- Connector with removable base, axial, or side cable entry, immediate assembly, and fixing using a locking ring**
- High degree of protection (IP66) and Shock resistance (IK05)**
- Fully flexible and interchangeable construction of up to 5 lens units (six colors of light lens unit)**

Image of product / Alternate images

Alternative

