







Product features and key data


Luminaire type	Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA.
Mounting method	Surface-mounting
Luminaire optic	The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface.
Light distribution curve	Lambertian (L)
FWHM	118,80 °
Light Engine	standard product
Colour temperature	4000 K
Rated luminous flux	2000 lm
Connected load	15,00 W
Luminous efficacy	133 lm/W
Rated service life	L80 (25 °C) = 100.000 h L90 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body sheet steel.
Electrical version	With electronic control gear unit, digitally dimmable (DALI).
DALI-2-Standard EN 62386	Yes
Connection method	Plug-in terminal
Number of DALI addresses	1
Dimming range	1 - 100 %
Monitoring Ready	Yes
Mains voltage	220 - 240 V
Mains frequency	50/60 Hz
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP40
Protection class	I
Impact resistance (IK)	IK03
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	14
Max. Luminaires B16	24
Max. Luminaires C10	24
Max. Luminaires C16	40
Net height	62,50 mm
Outside diameter	400 mm
Weight	2,1 kg

light distribution curve

Olisq RWD2 DW 20-840 ETDD


UGR I = 20,5
 UGR q = 20,5
 DIN 5040: B40
 UTE: 0.90 E + 0.10 T
 DLOR: 90 %
 ULOR: 10 %
 CEN Flux Code: 44 74 93 90 100 17 42 70 10


Olisq RWD2 DW 20-840 ETDD + Olisq RWD2 ZDR 1/1 03


UGR I = 21,8
 UGR q = 21,8
 DIN 5040: A40
 UTE: 1.00 E
 DLOR: 100 %
 ULOR: 0 %
 CEN Flux Code: 47 79 96 100 100 0 0 0 0


Olisq RWD2 DW 20-840 ETDD + Olisq RWD2 ZDR 1/1 01


UGR I = 21,8
 UGR q = 21,8
 DIN 5040: A40
 UTE: 1.00 E
 DLOR: 100 %
 ULOR: 0 %
 CEN Flux Code: 47 79 96 100 100 0 0 0 0


Olisq RWD2 DW 20-840 ETDD + Olisq RWD2 ZDR 1/1 05

UGR I = 21,8
 UGR q = 21,8
 DIN 5040: A40
 UTE: 1.00 E
 DLOR: 100 %
 ULOR: 0 %
 CEN Flux Code: 47 79 96 100 100 0 0 0 0


Olisq RWD2 DW 20-840 ETDD + Olisq RWD2 ZVF 03

UGR I = 22,3
 UGR q = 22,3
 DIN 5040: A40
 UTE: 1.00 E
 DLOR: 100 %
 ULOR: 0 %
 CEN Flux Code: 47 79 96 100 100 0 0 0 0


Olisq RWD2 DW 20-840 ETDD + Olisq RWD2 ZVF 05

UGR I = 22,3
 UGR q = 22,3
 DIN 5040: A40
 UTE: 1.00 E
 DLOR: 100 %
 ULOR: 0 %
 CEN Flux Code: 47 79 96 100 100 0 0 0 0

Available accessories

Material	Description
 ZSG 40 Vacuum Plug 2930500	Removal aid for glass covers or diffusers.
 Olisq RWD2 ZS DB 5075/1500 8224400	3-point wire suspension set. For luminaires from series Olisq RWD2...ETDD.
 Olisq RWD2 ZS DB 5075/3000 8224500	3-point wire suspension set. For luminaires from series Olisq RWD2...ETDD.
 Olisq RWD2 C 01 8225500	Semi-recessed housing for round surface-mounted luminaire Olisq RWD2... .
 Olisq RWD2 ZVF 01 8225900	Sheathing made of sheet steel. For luminaires from series Olisq RWD2... . Powder-coated surface, colour white. Other (RAL) colours on request.
 Olisq RWD2 ZDR 1/1 01 8226200	Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour white.
 Olisq RWD2 ZDR 1/2 01 8226600	Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour white.
 Wanne Olisq RWD2 Ersatz 8227100	Replacement diffuser for Wall and ceiling surface-mounted luminaires Olisq RWD2... .
 Wanne Olisq RWD2 PC Ersatz 8227200	Replacement diffuser for Wall and ceiling surface-mounted luminaires Olisq RWD2... .
 LEDM Olisq 360-830-01/R350 Ersatz 8228200	LED replacement module for luminaires of series Olisq RWD2... -830.
 LEDM Olisq 360-840-01/R350 Ersatz 8228300	LED replacement module for luminaires of series Olisq RWD2... -840.
 Olisq RWD2 ZVF 03 8269100	Sheathing made of sheet steel. For luminaires from series Olisq RWD2... . Powder-coated surface, colour silver-grey. Other (RAL) colours on request.
 Olisq RWD2 ZVF 05 8269400	Sheathing made of sheet steel. For luminaires from series Olisq RWD2... . Powder-coated surface, colour black. Other (RAL) colours on request.
 Olisq RWD2 ZDR 1/1 03 8269700	Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour silver-grey.
 Olisq RWD2 ZDR 1/1 05 8270700	Decorative attachment made of sheet steel. For covering the complete side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour black.
 Olisq RWD2 ZDR 1/2 03 8269900	Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour silver-grey.


Olisq RWD2 ZDR 1/2 05
 8270300

Decorative attachment made of sheet steel. For covering half the side surface. For luminaires from series Olisq RWD2... . Powder-coated surface, colour black.


Distanzstück Opendo D / 3331 D 01
 8443700

Spacer for surface-mounted luminaires. Construction height 18 mm. Colour white.

Offer text

Decorative, round surface-mounted luminaire with opal, cylindrical diffuser made of PMMA. Decorative attachments are available as optional accessories for precisely suitable light- and room scenes; these can also be implemented in custom colours on request. Developed and made in Germany. The luminaire is protected against vandalism in combination with the separately ordered accessory (ZVF...), and, when mounted to ceilings, is ball-proof in accordance with DIN 18032-3. For wall or ceiling mounting. With accessories to be ordered separately, also suitable for semi-recessed mounting (ceiling with cut-out) and suspended mounting. For protection as well as to assist with quick mounting, the components are arranged in the box in assembly order. The cover is quickly mounted on the mounting body without tools by click locking. The feed opening and fixing points mainly correspond to those of the series 740N, Mondia. The material and structure of the covering diffuser provide uniform and shadow-free illumination of the easy-to-clean luminaire surface. With Lambertian light distribution. With slight indirect component for surface illumination. Luminaire luminous flux and light color fixed. Luminaire luminous flux 2000 lm, connected load 15 W, maximum luminous efficiency of luminaire 133 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM. Mean rated service life L80 (t_q 25 °C) = 100,000 h., Mean rated service life L90 (t_q 25 °C) = 50,000 h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Replacement is without tools, the replacement light source can be obtained as a spare part. Luminaire body sheet steel. Surface coated white (similar to RAL 9016). Luminaire diameter Ø 400 mm, luminaire height 62,5 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP40, impact resistance level in accordance with IEC 62262: IK03, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Permissible ambient temperature (t_a): 25 °C Weight: 2,1 kg. With electronic control gear unit, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire is monitoring-ready (MOR), supplies luminaire data for monitoring or for predictive maintenance and is therefore compatible to the TRILUX Monitoring Services. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. Luminaire available for 10 years, spare parts (LED module, control gear unit, optical system) for 15 years from date of invoice, subject to reasonable modifications in the interests of progress.

EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class	Model identifier
D	SI-N8T281EB0EU
D	85401833-00